

# **VECTOR P HOOKED CAM**

This patented heavy-duty paddle latch is available with left, right or universal grip handle. The latching mechanism securely latch the cam behind the striker and the more force that is placed on the cam – the harder it will engage the striker.

Installed with a mounting bracket or four moulded-in bolts. IP66 water- and dust sealing. Key extraction: open/closed

Available with the inside release safety feature. This enables opening the latch from the inside even when it is locked.











### MATERIAL

Adapter for cylinder (internal component):

Glass fibre reinforced polyamide (PA6GF30)

**Body:** Glass fibre reinforced polyamide (PA6GF30)

Cam: Glass fibre reinforced polyamide

(PA6GF30)

Cast-in bolts: Steel, zinc plated

Cylinder: Zinc die cast, stainless steel 304 cap

and dust shutter

Gaskets: Polyurethane

**Handle:** Glass fibre reinforced polyamide

(PA6GF30)

Manoeuver arms: Zinc die cast, zinc plated

Mounting bracket: Steel, zinc plated

Nut: Steel, zinc plated

O-ring: NBR

Striker: Steel, zinc plated

#### **RELATED PRODUCTS**

Similar products: 2-834

Accessories: 2-412

Use the Index Code at industrilas.com


#### **TECHNICAL INFORMATION**


The tightening torque of the two nuts for the mounting bracket is 3,0 Nm. The tightening torque of the four nuts for the mould-in bolts is 2,2 Nm. It is important that the four holes made in the cut out for the mould-in bolts are within tolerance, to avoid damage when tightening the M5 nuts.

Standards: IP66, DIN EN 61373

**Cylinder information:** Cylinder with other key codes on request, Supplied with two keys







### CELATOR.COM.MX

## Make your selections in each column to create your article number (AAAA-BBCDDE-FFGG)

| AAAA Type            | BB Handle                                               | Material | C Mounting                          | DD Cam                                                                | E Type     | FF Cylinder                                                                                                                                                                                                                                                                                      | GG Striker H L                                                |
|----------------------|---------------------------------------------------------|----------|-------------------------------------|-----------------------------------------------------------------------|------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------|
| 2800 VECTOR - Paddle | 00 Universal 01 Universal 02 Universal 10 Left 20 Right |          | 1 Mould-in bolts 2 Mounting bracket | Fixed cam to prevent inside opening Cam with 03 inside safety release | O Standard | O1 Keyed alike 80 O2 Keyed alike 45 O3 Keyed to differ O6 Keyed alike 81 O7 Keyed alike 81 O7 Keyed alike 81 O7 Keyed alike 82 O7 Keyed alike 82 O7 Keyed alike 83 O7 Keyed alike 84 O7 Keyed alike 84 O7 Keyed alike 84 | 00 No 1 01 Yes 16 55  5 0 5 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 6 |

